


MP-LINEAR AC

IP66 **GRAZE**

The built in power supply makes the installation easier,
 Compact design for limited space with high consistency of light out put,
 Various beam angles are available for balancing efficiency and lighting effects,
 Connection extension can be up to 38 meters.



-  RGBW
-  Dimmable
-  Adjustable
-  IP66
-  Easy Installation
-  RDM
-  Extreme Environments
-  AC-IN







SPECIFICATION

MODEL	▶ MP-LINEAR AC
OPERATING VOLTAGE	▶ AC 100-240V
POWER CONSUMPTION	▶ 9W/320mm, 36W/1220mm
LED TYPE	▶ High Power LED
COLOR RANGE	▶ 2700K,3000K,3500K,4000K,5000K,Tunable White,RGBW,RGBA
CRI	▶ 90min, 80min
SYSTEM EFFICIENCY	▶ 78lm/W@3000K
FWHM	▶ Tilt 2.5@11°, 6°, 8°*15°, 8°*30°, 8°*50°, 20°*40°, 25°, 45°, 60°
MATERIAL	▶ Aluminum + Tempered Glass
OPERATING TEMPERATURE	▶ -20°C ~ +55°C
STORAGE TEMPERATURE	▶ -25°C ~ +60°C
LIFE TIME	▶ 50,000 hours/L70 at 25°C
CONNECTION	▶ Quick-Plug
DIMENSIONS	▶ 1220(L)*35(W)*61(H)mm, 320/620/920mm available
CABLE LENGTH	▶ 150mm
WATER PROOF	▶ IP66
CONTROL	▶ ON/OFF, DMX/RDM, Triac Dim, 0-10V Dim
LIST	▶ CE


ORDER CODE	MODEL	LENGTH	POWER	CCT	CRI	OPTICS	VOLTAGE	CONTROL	ACC
EXAMPLE	MP-LINEAR AC	- 1220	- 36	- 3000K	- 90	- 6	- 220	- DMX	- LOUVER

DIMENSIONS

Unit: mm



Louver



Barn Door(BD)



Leader Cable



Jumper Cable



OPTIC SELECTION



6°

LED	Lumens	Watts	Efficacy
WHITE	2521.76	36.00	70.04

CenterBeamLux	Illuminance at Distance
7777.77 lx	5.0m
1944.44 lx	10.0m
864.20 lx	15.0m
486.11 lx	20.0m
311.11 lx	25.0m
216.05 lx	30.0m

■ Ver. Spread: 5.7° ■ Horiz. Spread: 5.7°



8°X50°

LED	Lumens	Watts	Efficacy
WHITE	2628.00	36.00	73.00

CenterBeamLux	Illuminance at Distance
836.36 lx	5.0m
209.09 lx	10.0m
92.93 lx	15.0m
52.27 lx	20.0m
33.45 lx	25.0m
23.23 lx	30.0m

■ Ver. Spread: 6.5° ■ Horiz. Spread: 48.5°

3000K