

DECK 19

IP67 **LANDSCAPE**

Designed to be sophisticated yet mini,
The system generates sparkling cosmo effects
for ground or wall decoration,
Safe voltage: 12V DC,
The body is made from marine grade Stainless Steel 316.



RGBW



Extreme
Environments



Dimmable



IP67



Easy
Installation





SPECIFICATION

MODEL	▶ DECK 19
OPERATING VOLTAGE	▶ 12V DC
POWER CONSUMPTION	▶ 0.5W,1W
LED TYPE	▶ High Power LED
COLOR RANGE	▶ 2700K,3000K,4000K,5000K,Tunable White,RGB,RGBW
PIXEL	▶ 80min
SYSTEM EFFICIENCY	▶ 75lm/W@3000K
FWHM	▶ 40°,60°,80°,120°
MATERIAL	▶ Stainless Steel 316 + Tempered Glass
PROTECTION	▶ IK08
OPERATING TEMPERATURE	▶ -20°C ~ +55°C
STORAGE TEMPERATURE	▶ -25°C ~ +60°C
LIFE TIME	▶ 50,000 hours/L70 at 25°C
DIMENSIONS	▶ Φ24*30(H)mm (120° & ON/OFF only) Φ24*48(H)mm
CABLE LENGTH	▶ 500mm
WATER PROOF	▶ IP67
CONTROL	▶ ON/OFF, DMX, 0-10V Dim
LIST	▶ CE


ORDER CODE	MODEL	POWER	CCT	CRI	OPTICS	VOLTAGE	CONTROL	ACC
EXAMPLE	DECK 19	- 1	- 3000K	- 80	- 120	- 12	- ON/OFF	

DIMENSIONS

Unit: mm




120° & ON/OFF only



Half Moon Glass



Full Moon Glass



Cut Out 19mm

OPTIC SELECTION



80°

LED	Lumens	Watts	Efficacy
WHITE	37.50	0.50	75.00

CenterBeamLux	Illuminance at Distance
870.90 lx	0.2m
217.70 lx	0.3m
97.76 lx	0.5m
54.42 lx	0.7m
34.84 lx	0.8m
24.19 lx	1.0m

■ Ver. Spread: 82.4° ■ Horiz. Spread: 82.2°



120°

LED	Lumens	Watts	Efficacy
WHITE	70.00	1.00	70.00

CenterBeamLux	Illuminance at Distance
170.85 lx	0.2m
60.27 lx	0.3m
21.24 lx	0.5m
11.59 lx	0.7m
9.19 lx	0.8m
6.25 lx	1.0m

■ Ver. Spread: 112.7° ■ Horiz. Spread: 114.0°

3000K