

INGROUND 200

IP67 **LANDSCAPE**

Sophisticated design makes for easy beam angle adjustments,
Excellent glare control via louver,
The compact structure provides easy installation and maintenance.



Dimmable



Adjustable



IP67



Easy Installation






SPECIFICATION

MODEL	▶ INGROUND 200
OPERATING VOLTAGE	▶ 24V DC
POWER CONSUMPTION	▶ 25W Max
LED TYPE	▶ COB,High Power LED
COLOR RANGE	▶ 2700K,3000K,3500K,4000K,5000K
CRI	▶ 90min,80min
SYSTEM EFFICIENCY	▶ 75lm/W@3000K
FWHM	▶ 10°, 15°, 25°, 30°, 45°
MATERIAL	▶ Aluminum + Stainless Steel 316L + Tempered Glass
PROTECTION	▶ IK10
OPERATING TEMPERATURE	▶ -20°C ~ +55°C
STORAGE TEMPERATURE	▶ -25°C ~ +60°C
LIFE TIME	▶ 50,000 hours/L70 at 25°C
DIMENSIONS	▶ Φ200*153(H)mm
CABLE LENGTH	▶ 300mm
WATER PROOF	▶ IP67
CONTROL	▶ ON/OFF, DMX, 0-10V Dim
LIST	▶ CE


ORDER CODE	MODEL	POWER	CCT	CRI	OPTICS	VOLTAGE	CONTROL	ACC
EXAMPLE	INGROUND 200	- 25	- 3000K	- 80	- 15	- 24	- ON/OFF	- HC

DIMENSIONS


Unit: mm




Pre installation Kit(PIKS)



Honey Comb(HC)



Adjustable



Cut Out 193mm

OPTIC SELECTION



15°

LED	Lumens	Watts	Efficacy
WHITE	1880.00	25.00	75.20

CenterBeamLux	Illuminance at Distance
35925.11 lx	0.8m
8981.28 lx	1.7m
3991.68 lx	2.5m
2245.32 lx	3.3m
1437.01 lx	4.2m
997.92 lx	5.0m

■ Ver. Spread: 14.1° ■ Horiz. Spread: 14.1°



25°

LED	Lumens	Watts	Efficacy
WHITE	1813.09	25.00	72.52

CenterBeamLux	Illuminance at Distance
8681.47 lx	0.8m
2170.37 lx	1.7m
965.45 lx	2.5m
542.59 lx	3.3m
347.26 lx	4.2m
241.15 lx	5.0m

■ Ver. Spread: 25.8° ■ Horiz. Spread: 24.7°

3000K