

WALL LIGHT 36R

IP67 **LANDSCAPE**

Designed to be sophisticated yet mini,
The system generates sparkling cosmo effects
wall decoration,
Safe voltage: 12V DC,



RGBW



Extreme
Environments



Dimmable



IP67



Easy
Installation



SPECIFICATION

MODEL	▶ WALL LIGHT 36R
OPERATING VOLTAGE	▶ 12V DC, 24V DC
POWER CONSUMPTION	▶ 0.5W, 1W, 1.5W
LED TYPE	▶ High Power LED
COLOR RANGE	▶ 2700K,3000K,4000K,5000K,Tunable White,RGB,RGBW
CRI	▶ 80min
SYSTEM EFFICIENCY	▶ 52lm/W@3000K
FWHM	▶ 25°,40°,60°,80°,120°,Asymmetric
MATERIAL	▶ Aluminum
PROTECTION	▶ IK08
OPERATING TEMPERATURE	▶ -20°C ~ +55°C
STORAGE TEMPERATURE	▶ -25°C ~ +60°C
LIFE TIME	▶ 50,000 hours/L70 at 25°C
DIMENSIONS	▶ Φ36*28(H)mm(Recessed Mounting) ▶ Φ36*35(H)mm(Pre installation Kit Mounting)
CABLE LENGTH	▶ 300mm
WATER PROOF	▶ IP67
CONTROL	▶ ON/OFF, DMX (Remote), 0-10V Dim
LIST	▶ CE




ORDER CODE	MODEL	POWER	CCT	CRI	OPTICS	VOLTAGE	CONTROL	ACC
------------	-------	-------	-----	-----	--------	---------	---------	-----

EXAMPLE	WALL LIGHT 36R	-	1	-	3000K	-	80	-	120	-	12	-	ON/OFF
---------	----------------	---	---	---	-------	---	----	---	-----	---	----	---	--------

DIMENSIONS




Unit: mm

Pre installation Kit Mounting



Pre installation Kit(PIKS)

Recessed Mounting



Cut Out 30mm

OPTIC SELECTION



40°

LED	Lumens	Watts	Efficacy
WHITE	26.00	0.50	52.00

CenterBeamLux	Illuminance at Distance
1073.50 lx	0.2m
269.28 lx	0.3m
118.94 lx	0.5m
66.88 lx	0.7m
42.94 lx	0.8m
29.83 lx	1.0m

■ Ver. Spread: 42.4° ■ Horiz. Spread: 42.2°



120°

LED	Lumens	Watts	Efficacy
WHITE	22.50	0.50	45.00

CenterBeamLux	Illuminance at Distance
59.55 lx	0.2m
21.07 lx	0.3m
7.43 lx	0.5m
4.02 lx	0.7m
3.21 lx	0.8m
2.18 lx	1.0m

■ Ver. Spread: 112.3° ■ Horiz. Spread: 114.0°

3000K