

INGROUND SLIM G2

IP67 **LANDSCAPE**

Uniform light output via 3 steps bin selection upon request,
The high quality diffuser eliminates any visible LED hotspots,
straight icon and ensures superb illumination,
The system provides step-on tempered glass for inground installations,
A seamless continuous connection for lighting.



RGBW



Diffused



Dimmable



IP67



Easy
Installation

SPECIFICATION

MODEL	▶ INGROUND SLIM G2
OPERATING VOLTAGE	▶ 12V DC, 24V DC
POWER CONSUMPTION	▶ 5W/meter, 9.6W/meter, 14.4W/meter
LED TYPE	▶ SMD
COLOR RANGE	▶ 2400K,2700K,3000K,4000K,5000K,Tunable White,RGB,RGBW
CRI	▶ 80min, 90min
SYSTEM EFFICIENCY	▶ 82lm/W@3000K
FWHM	▶ 120°
MATERIAL	▶ Stainless Steel + Tempered Glass
PROTECTION	▶ IK10
OPERATING TEMPERATURE	▶ -20°C ~ +55°C
STORAGE TEMPERATURE	▶ -25°C ~ +60°C
LIFE TIME	▶ 50,000 hours/L70 at 25°C
CONNECTION	▶ Quick-Plug
DIMENSIONS	▶ 1000(L)*30(W)*90~125(H)mm, 300/600/900/1200mm available
CABLE LENGTH	▶ 300mm
WATER PROOF	▶ IP67
CONTROL	▶ ON/OFF, DMX, 0-10V Dim
LIST	▶ CE

ORDER CODE	MODEL	LENGTH	POWER	CCT	CRI	OPTICS	VOLTAGE	CONTROL	ACC
EXAMPLE	INGROUND SLIM G2	- 1000	- 9.6	- 3000K	- 80	- 120	- 24	- ON/OFF	

DIMENSIONS



Unit: mm



Leader Cable



Jumper Cable



OPTIC SELECTION



120°

LED	Lumens	Watts	Efficacy
WHITE	788.92	9.60	82.18

CenterBeamLux	Illuminance at Distance
2721.50 lx	0.3m
679.97 lx	0.7m
302.38 lx	1.0m
170.09 lx	1.3m
108.79 lx	1.7m
75.59 lx	2.0m

■ Ver. Spread: 112.7° ■ Horiz. Spread: 114.0°

3000K



120°

LED	Lumens	Watts	Efficacy
RGBW	651.90	9.60	67.90

CenterBeamLux	Illuminance at Distance
2007.18 lx	0.3m
501.80 lx	0.7m
223.02 lx	1.0m
125.45 lx	1.3m
80.29 lx	1.7m
55.76 lx	2.0m

■ Ver. Spread: 112.7° ■ Horiz. Spread: 114.0°

