






INGROUND GRAZE 34

IP67 **LANDSCAPE**

Sophisticated designed anti-glare structure provides linear inground wall grazing perfectly,
 IP patented fixture offers consistent light without hazardous glare,
 Robust walk over design for inground installation.



-  RGBW
-  Dimmable
-  Extreme Environments
-  IP67
-  Easy Installation




SPECIFICATION

MODEL	› INGROUND GRAZE 34
OPERATING VOLTAGE	› 24V DC, 48V DC
POWER CONSUMPTION	› 18W/1000mm, 30W/1000mm
LED TYPE	› SMD, High Power LED
COLOR RANGE	› 2700K,3000K,4000K,5000K,Tunable White,RGB,RGBW
CRI	› 90min, 80min
SYSTEM EFFICIENCY	› 56lm/W@3000K(Integrated Lens), 78lm/W@3000K(Single Lens)
FWHM	› 20°*90° (Integrated Lens), 10°, 20°*60°, 25°
MATERIAL	› Aluminum + Tempered Glass
PROTECTION	› IK10
OPERATING TEMPERATURE	› -20°C ~ +55°C
STORAGE TEMPERATURE	› -25°C ~ +60°C
LIFE TIME	› 50,000 hours/L70 at 25°C
CONNECTION	› Quick-Plug
DIMENSIONS	› 1000(L)*34(W)*90~125(H)mm 300/500/900/1200mm ETO available
CABLE LENGTH	› 300mm
WATER PROOF	› IP67
CONTROL	› ON/OFF, DMX (Remote), 0-10V Dim
LIST	› CE

ORDER CODE	MODEL	LENGTH	POWER	CCT	CRI	OPTICS	VOLTAGE	CONTROL	ACC
EXAMPLE	INGROUND GRAZE 34	- 1000	- 30	- 3000K	- 90	- 2090	- 24	- ON/OFF	


DIMENSIONS

Unit: mm




Stainless Steel Kit


Micro Louver Inside(MLI)



Honey Comb Inside(HCI)



Leader Cable



* DMX/0-10V remote PSU control

OPTIC SELECTION



20°X90°

LED	Lumens	Watts	Efficacy
WHITE	1590.00	30.00	53.00

CenterBeamLux	Illuminance at Distance
3103.28 lx	0.8m
774.38 lx	1.7m
448.20 lx	2.5m
340.88 lx	3.3m
400.08 lx	4.2m
87.86 lx	5.0m

■ Ver. Spread: 20.0° ■ Horiz. Spread: 90.5°

2700K



20°X90°

LED	Lumens	Watts	Efficacy
WHITE	1689.00	30.00	56.30

CenterBeamLux	Illuminance at Distance
3923.03 lx	0.8m
735.16 lx	1.7m
434.34 lx	2.5m
244.80 lx	3.3m
156.46 lx	4.2m
107.95 lx	5.0m

■ Ver. Spread: 20.0° ■ Horiz. Spread: 90.5°

3000K